

Connection	Flow Factor	Models/Connections			Dia. (mm)	Min. Dia. (mm)	US (gpm at 40 psi)	Pressure (Bar)								Angle <° 3 Bar
		Female		Male				0,5	1	2	3	4	6	8	10	
		FB4	FB4LC	MB4				Capacity (Lpm)								
1/4"	14			●	3,6	1,6	2,53	4,08	5,77	8,16	10,00	11,55	14,14	16,33	18,26	100
3/8"	20			●	4,4	2,4	3,67	5,92	8,37	11,84	14,50	16,74	20,51	23,68	26,47	110
1/2"	35			●	5,9	3,2	6,31	10,17	14,38	20,33	24,90	28,75	35,21	40,66	45,46	110
3/4"	71	●		●	9,8	4,4	12,64	20,37	28,81	40,74	49,90	57,62	70,57	81,49	91,10	110
1"	130	●		●	13,1	5,6	23,56	37,97	53,69	75,93	93,00	107,39	131,52	151,87	169,79	110
1-1/4"	190		●		15,5	5,6	34,20	55,11	77,94	110,23	135,00	155,88	190,92	220,45	246,48	110
1-1/2"	290		●		18,2	8	50,92	82,06	116,05	164,12	201,00	232,09	284,26	328,23	366,97	110
2"	560		●		25	11,2	99,81	160,85	227,48	321,70	394,00	454,95	557,20	643,40	719,34	110
2-1/2"	830		●		31,8	14,4	149,46	240,87	340,64	481,73	590,00	681,27	834,39	963,47	1.077,19	110