

TYPE OF NOZZLE	Ø1 mm	Ø2 mm	PRESSURE (bar)									bar		
			0.75	1	1.5	2	3	4	5	6	7	0.5	1.5	5
			CAPACITY (l/min)									°	°	°
* 1 1/4 F - B1 - 6	17.6	6.5	28	31	38	48	51	60	66	73	78	48	50	45
* 1 1/4 F - B1 - 10	19.5	6.4	47	52	62	72	87	100	110	121	129	65	68	60
* 1 1/4 F - B1 - 12	10.6	6.5	57	63	76	87	105	120	132	145	155	65	70	62
* 1 1/4 F - B1 - 14	12.4	6.5	66	73	88	100	122	140	155	168	180	77	80	73
* 1 1/4 F - B1 - 20	15	8	95	105	125	145	174	199	221	240	255	90	95	85
* 1 1/2 F - B1 - 10	9.6	8.8	47	52	62	72	87	100	110	121	129	48	5	45
* 1 1/2 F - B1 - 16	12.6	8.8	76	84	100	115	140	160	175	192	205	72	75	65
* 1 1/2 F - B1 - 20	14.2	8.8	95	105	125	145	174	199	221	240	255	75	77	70
* 1 1/2 F - B1 - 30	18.2	10.3	142	157	190	215	260	300	330	360	386	90	95	85
* 2 F - B1 - 17	12.6	11.2	80	89	107	125	148	170	170	205	220	48	50	45
* 2 F - B1 - 30	17.2	11.2	142	157	190	215	260	300	300	360	386	70	75	65
* 2 F - B1 - 35	19.1	11.2	168	184	220	250	305	345	345	421	450	75	77	70
* 2 F - B1 - 40	22.0	11.2	190	210	250	290	348	398	398	480	510	78	80	75
* 2 F - B1 - 50	23.7	14.4	236	260	315	361	434	495	495	600	642	83	85	78
* 2 F - B1 - 60	28.5	14.4	280	310	380	430	510	600	600	730	780	98	100	90
* 2 1/2 F - B1 - 25	15.0	14.4	119	131	158	180	215	250	250	300	322	48	50	45
* 2 1/2 F - B1 - 50	22.1	14.4	236	260	315	361	434	495	495	600	642	70	75	65
* 2 1/2 F - B1 - 60	24.5	14.4	280	310	380	430	510	600	600	730	780	75	78	72
* 2 1/2 F - B1 - 70	28.5	14.4	331	365	440	510	510	700	700	838	900	80	85	75
* 2 1/2 F - B1 - 80	28.5	14.4	381	420	510	580	705	800	800	960	1030	85	88	80
* 2 1/2 F - B1 - 90	31.7	14.4	427	470	570	650	780	890	890	1080	1160	95	98	90