

Connection	Flow Factor	Models/Connections				Dia. (mm)	Min. Dia. (mm)	US (gpm at 40 psi)	Pressure (Bar)								Angle <° 3 Bar
		Female		Male					0,5	1	2	3	4	6	8	10	
		FBB5	FBB6	MBB5	MBB6				Capacity (Lpm)								
1/8"	<b>2</b>	●		●		1,3	1,0	0,38	0,61	0,87	1,22	<b>1,50</b>	1,73	2,12	2,45	2,74	50
1/8"	<b>3</b>	●		●		1,6	1,0	0,56	0,90	1,27	1,80	<b>2,20</b>	2,54	3,11	3,59	4,02	65
1/8"	<b>3,5</b>	●		●		1,6	1,0	0,63	1,02	1,44	2,04	<b>2,50</b>	2,89	3,54	4,08	4,56	50
1/8"	<b>5</b>	●		●		2,0	1,3	0,95	1,53	2,17	3,06	<b>3,75</b>	4,33	5,30	6,12	6,85	65
1/4"	<b>5</b>			●		2,0	1,3	0,95	1,53	2,17	3,06	<b>3,75</b>	4,33	5,30	6,12	6,85	65
1/4"	<b>6,5</b>	●		●		2,3	1,6	1,23	1,98	2,80	3,96	<b>4,85</b>	5,60	6,86	7,92	8,85	50
1/4"	<b>10</b>	●		●		2,9	1,6	1,90	3,06	4,33	6,12	<b>7,50</b>	8,66	10,61	12,25	13,69	65
3/8"	<b>9,5</b>	●		●		2,6	2,4	1,80	2,90	4,10	5,80	<b>7,10</b>	8,20	10,04	11,59	12,96	50
3/8"	<b>15</b>	●		●		3,6	2,4	2,84	4,57	6,47	9,14	<b>11,20</b>	12,93	15,84	18,29	20,45	65
3/8"	<b>20</b>	●		●		4,0	2,8	3,75	6,04	8,54	12,08	<b>14,80</b>	17,09	20,93	24,17	27,02	80
3/8"	<b>22</b>	●		●		4,7	2,8	4,10	6,61	9,35	13,23	<b>16,20</b>	18,71	22,91	26,45	29,58	85
1/2"	<b>16</b>	●		●		3,5	3,2	3,01	4,86	6,87	9,72	<b>11,90</b>	13,74	16,83	19,43	21,73	60
1/2"	<b>25</b>	●		●		4,6	3,2	4,66	7,51	10,62	15,02	<b>18,40</b>	21,25	26,02	30,05	33,59	75
1/2"	<b>32</b>	●		●		5,2	3,6	6,05	9,76	13,80	19,51	<b>23,90</b>	27,60	33,80	39,03	43,64	85
1/2"	<b>40</b>	●		●		6,4	3,6	7,50	12,08	17,09	24,17	<b>29,60</b>	34,18	41,86	48,34	54,04	90
1/2"	<b>50</b>	●		●		6,7	4,3	9,50	15,31	21,65	30,62	<b>37,50</b>	43,30	53,03	61,24	68,47	90
1/8"	<b>4,3</b>		●		●	2,0	1,0	0,79	1,27	1,79	2,53	<b>3,10</b>	3,58	4,38	5,06	5,66	110
1/8"	<b>8</b>		●		●	2,5	1,3	1,42	2,29	3,23	4,57	<b>5,60</b>	6,47	7,92	9,14	10,22	110
1/4"	<b>14</b>		●		●	3,6	1,6	2,58	4,16	5,89	8,33	<b>10,20</b>	11,78	14,42	16,66	18,62	110
3/8"	<b>20</b>		●		●	4,4	2,4	3,67	5,92	8,37	11,84	<b>14,50</b>	16,74	20,51	23,68	26,47	110
1/2"	<b>35</b>		●		●	5,9	3,2	6,28	10,12	14,32	20,25	<b>24,80</b>	28,64	35,07	40,50	45,28	110
1/2"	<b>50</b>		●		●	6,7	4,3	9,20	14,82	20,96	29,64	<b>36,30</b>	41,92	51,34	59,28	66,27	110